



Face mount connection to web

The top flange of the supporting joist must be supported by backer blocks to prevent cross grain bending and rotation



Top mount connection

Joists series	Flange width (mm)	Joist depth (mm)	Net filler block size (mm x mm)
RFPI 20	45	240	35 x 150
		300	35 x 200
		360	35 x 250
RFPI 400	52	240	45 x 150
		300	45 x 200
		360	45 x 250
RFPI 70	58	240	50 x 150
		300	50 x 200
		360	50 x 250
RFPI 90	90	400	50 x 300
		300	75 x 200
		360	75 x 250
		400	75 x 300

your partner for engineered timber solutions

DINDAS AUSTRALIA
ENGINEERING DIVISION

433 Wondall Road, Tingalpa 4173, Queensland

DATE CREATED: 28/07/2020

DRAWN BY: B.S

CHECKED BY: --

DWG REV: --

TITLE: I-JOIST TO TRIMMER CONNECTION

DETAIL 1H

NOTES:

- Dimensions are in millimetres.
- Tolerance on all dimensions to be +/- 0,5mm unless noted otherwise.
- Written dimensions take precedence over scaled dimensions.

Private Confidential & Copyright
This drawing is the exclusive property of Dindas Australia. Copyright & all rights reserved. You hereby agree and undertake that you will not in anyway utilize, copy reproduce or take advantage of the drawing (or any part thereof) and disclose any information to other parties without the written consent of Dindas Australia.

SIZE A4

SCALE N.T.S