

DINDASBRACE OSB

6.0mm OSB Panel Bracing

DINDAS
Australia



DINDASBRACE OSB, by Dindas Australia, are Oriented Strand Board (OSB/3), oriented strands according to EN 300. It uses cutting-edge manufacturing technology from Germany, and it is engineered for its strength, durability and consistent performance.



High-Performance Engineered Wood Product

- Each piece is highly consistent in the way it performs under load.
- Manufactured with type 'A' (marine) bond, renowned for its structural strength and long-lasting durability.
- Sealed edge protection that effectively prevents moisture ingress.



Design Capabilities

- 6.0mm bracing is designed for simple bracing solutions, and it has up to 6 kN/m racking resistance.
- Design Guide details and identification of bracing capacities have been created to reflect that of table 8.18 of AS1684.2-2021.
- Features a solid construction that is both sturdy and lightweight, ensuring maximum stability and durability.



Certification

- Independently tested in Australia through our Certified University Partner program.
- It is an independently certified product that meets the requirements of the NCC and is manufactured to BS EN300:2006, meeting the performance characteristics for load-bearing (structural) application in dry and humid conditions.



Sustainable Sourcing

- As a Carbon Warrior partner, we only work with suppliers with verified Wood Source Certifications for responsible and sustainable timber.
- Chain of Custody certification compliant for well-managed and sustainable forests.



Product Specs


APPLICATIONS: Exterior.


DindasBrace OSB is a versatile product with a wide range of construction applications, but it is mainly used as Structural Wall Bracing.

TREATMENTS: Available as Untreated & H2 Treated

STANDARDS: AS1684.2-2021 and EN300:2006

CERTIFICATIONS: 100% Chain of Custody (COC) compliant well, well-managed, and sustainable forests.

 Easy to identify H2 Treatment with Red edges

 Easy to identify UT with Green edges



Scan to access our complete DindasBrace OSB Product Guide

Advantages


- High Mechanical Strength.
- Internationally recognised.
- Third-party certification.
- Structural Support In Building Construction.
- It's easy to handle
- It's easy to fix and nail.
- It can be installed quickly.
- Termite resistant
- Moisture resistant surface coating
- It's Strong & durable.
- It offers a safe formaldehyde-free resin.

6.0 mm DINDASBRACE OSB Size		Pieces per pack	Area per pack (m2)	Weight/panel (kg)	Weight/pack (kg)
Length (mm)	Width (mm)				
2440	900	100	219.6	9	900
2440	1200	100	292.8	11.9	1190
2745	900	100	246.6	10.1	1010
2745	1200	100	328.8	13.4	1340
3050	900	100	274.5	11.2	1120
3050	1200	100	366.0	14.9	1490

DindasOSB Brace can also be supplied in handy 50 piece packs by request.

For more information visit dindas.com.au

 DindasAustralia

 dindas_australia

VICTORIA (Head-Office)

58 Whiteside Road, Clayton Sth
 Phone 03 8540 0500
 Fax 03 8540 0599
vicsales@dindas.com.au

QUEENSLAND

433 Wondall Road, Tingalpa
 Phone 07 3249 9888
 Fax 07 3249 9899
qldsales@dindas.com.au

NEW SOUTH WALES

138 Dunheved Circuit, St Marys
 Phone 02 9673 8000
 Fax 02 9673 8099
nswsales@dindas.com.au